

General

Location:	Interior
Class:	CE (Class I)
IP-rating:	IP20
Driver included:	Yes
Installation orientation:	Ceiling mount
Main material:	Aluminium powder coated RAL9016
Dimensions (mm):	H: 520mm W: 190mm D: 40mm
Cut out hole (mm):	-
Recess depth (mm):	-
Lamp included:	Yes
Dimmable:	Yes
Dimming method:	Mains dimmable (See catalog for other options)

Models



CODE WL04 0102 LED (*)

White Line AR48 quadra line
 2700K - CRI>97
 4xLED 4W - 1600lm - 350mA



CODE WL04 0102 LEDH (*)

White Line AR48 quadra line - high ring
 2700K - CRI>97
 4xLED 4W - 1600lm - 350mA



CODE WL04 0102 LEDDTW (*)

White Line AR48 quadra line - dim to warm
 2800K-1800K - CRI>95
 4xLED 4W - 1920lm - 250mA



CODE WL04 0102 LEDHDTW (*)

White Line AR48 quadra line - high ring - dim to warm
 2800K-1800K - CRI>95
 4xLED 4W - 1920lm - 250mA

Required options (*)

WL H40 REFLECTOR	Spot 19° or Flood 34°
------------------	-----------------------