



Surface mounted round - driver excl.

Dotsi ø38mm | surface mounted round | excl. driver | tube small



| | 2700K CRI97 | 3000K CRI97 |
|---------------|--------------------|--------------------|
| | 6W · 425lm · 24Vdc | 6W · 450lm · 24Vdc |
| White RAL9016 | WLDOTSI 1001010101 | WLDOTSI 1001010102 |
| Ano black | WLDOTSI 1002010101 | WLDOTSI 1002010102 |
| Ano champagne | WLDOTSI 1003010101 | WLDOTSI 1003010102 |
| Ano bronze | WLDOTSI 1004010101 | WLDOTSI 1004010102 |

Dotsi ø38mm | surface mounted round | excl. driver | tube large



| | 2700K CRI97 | 3000K CRI97 |
|---------------|--------------------|--------------------|
| | 6W · 425lm · 24Vdc | 6W · 450lm · 24Vdc |
| White RAL9016 | WLDOTSI 1001030101 | WLDOTSI 1001030102 |
| Ano black | WLDOTSI 1002030101 | WLDOTSI 1002030102 |
| Ano champagne | WLDOTSI 1003030101 | WLDOTSI 1003030102 |
| Ano bronze | WLDOTSI 1004030101 | WLDOTSI 1004030102 |

Installation accessories

Required lens options

| Item code | Description |
|------------------|-------------------------------|
| WLDOTSI 01LENS01 | Lens for Dotsi ø38mm - 15° |
| WLDOTSI 01LENS02 | Lens for Dotsi ø38mm - 20° |
| WLDOTSI 01LENS03 | Lens for Dotsi ø38mm - 30° |
| WLDOTSI 01LENS04 | Lens for Dotsi ø38mm - 40° |
| WLDOTSI 01LENS05 | Lens for Dotsi ø38mm - 45x20° |

Required driver options 24Vdc

| Item code | Description | Min | Max |
|------------------------|--|-----|------|
| NON DIM | | | |
| WL DRIVER17 | WL Driver17 24Vdc 12W (1pcs) (non-dim) | 1 | 2 * |
| MAINS DIM | | | |
| WL DRIVER13 | WL Driver13 24Vdc 36W (1pcs) (mains dim) | 1 | 5 * |
| WL DRIVER16 | WL Driver16 24Vdc 60W (1pcs) (mains dim) | 1 | 9 * |
| 1-10V/DALI/PUSH | | | |
| WL DRIVER14 | WL Driver14 24Vdc 70W (1pcs) (1-10V/DALI dim) | 1 | 10 * |
| WL DRIVER19 | WL Driver19 24Vdc 120W (1pcs) (1-10V/DALI dim) | 1 | 15 * |

(*) driver does not fit inside ceiling box

pvdconcept[®]

White Line Dotsi 38