





Tubed surface mounted round - driver excl.

Dotsi ø38mm | tubed surface mounted round | excl. driver | tube small



	2700K CRI97	3000K CRI97
	6W · 425lm · 24Vdc	6W · 450lm · 24Vdc
White RAL9016	WLDOTSI 1401010101	WLDOTSI 1401010102
Ano black	WLDOTSI 1402010101	WLDOTSI 1402010102
Ano champagne	WLDOTSI 1403010101	WLDOTSI 1403010102
Ano bronze	WLDOTSI 1404010101	WLDOTSI 1404010102

Dotsi ø38mm | tubed surface mounted round | excl. driver | tube large



	2700K CRI97	3000K CRI97
	6W · 425lm · 24Vdc	6W · 450lm · 24Vdc
White RAL9016	WLDOTSI 1401030101	WLDOTSI 1401030102
Ano black	WLDOTSI 1402030101	WLDOTSI 1402030102
Ano champagne	WLDOTSI 1403030101	WLDOTSI 1403030102
Ano bronze	WLDOTSI 1404030101	WLDOTSI 1404030102

Installation accessories

Required lens options

Item code	Description
WLDOTSI 01LENS01	Lens for Dotsi ø38mm - 15°
WLDOTSI 01LENS02	Lens for Dotsi ø38mm - 20°
WLDOTSI 01LENS03	Lens for Dotsi ø38mm - 30°
WLDOTSI 01LENS04	Lens for Dotsi ø38mm - 40°
WLDOTSI 01LENS05	Lens for Dotsi ø38mm - 45x20°

Required driver options 24Vdc

Item code	Description	Min	Max
NON DIM			
WL DRIVER17	WL Driver17 24Vdc 12W (1pcs) (non-dim)	1	2 *
MAINS DIM			
WL DRIVER13	WL Driver13 24Vdc 36W (1pcs) (mains dim)	1	5 *
WL DRIVER16	WL Driver16 24Vdc 60W (1pcs) (mains dim)	1	9 *
1-10V/DALI/PUSH			
WL DRIVER14	WL Driver14 24Vdc 70W (1pcs) (1-10V/DALI dim)	1	10 *
WL DRIVER19	WL Driver19 24Vdc 120W (1pcs) (1-10V/DALI dim)	1	15 *

(*) driver does not fit inside ceiling box

pvdconcept[®]

White Line Dotsi 38